

What is the aim OBDII 2m external power cable used for?

The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables available for the Solo 2 DL. Others are the RS232/CAN and the RPM cable. Some of the OBDII protocol channels received are RPM, Vehicle speed, Fuel level, Throttle position.

Can I plug my aim Solo / Solo 2 DL into a plug and play adapter?

Pre-assembled AiM Solo / Solo 2 DL cable to be used in conjunction with our plug and play adapters. This pre-assembled cable with mating 4-pin Deutsch DTM connector will allow you to directly plug your AiM Solo or Solo 2 DL into one of our plug and play adapters, providing: CAN-Hi and CAN-Low for logging of additional vehicle parameters

How to connect Solo 2 DL to AiM LCU One CAN?

To connect Solo 2 DL to AiM LCU One CAN, plug the 5 pins male Binder connector of LCU one in the female one bottom left. Solo 2 DL can communicate using all currently available communication lines: CAN, etc.

Can a can/rs232 DL / solo 2 DL plug into a CAN-bus adapter?

This cable is included with a CAN/RS232 Solo DL / Solo 2 DL but is unterminated and will not be able to directly plug into one of our 4-pin CAN-Bus adapters. If you already have one of these cables you can send it to us before (usable condition) or after (original condition) your order to receive a refund of the cable itself.

Solo 2 DL: Solo 2 DL, power cable with AC adapter, mounting bracket with screws, user manual, software installation CD, AiM sticker. Concerning the cables you can choose among: CAN/K-Line/External power ...

Shop AiM Solo 2 DL CAN / RS232 2M External Power Lead online today to enhance your racing setup. Shop high-quality motorsport data logging systems with next day delivery options available. ... AiM Solo 2 DL CAN / RS232 2M ...

Available kits are: Solo kit, Solo DL OBD (K+CAN line) and SoloDL CAN/RS232 kits. The images below show all kits with all included items numbered. Solo kit part number is ...

AiM Solo 2 DL RPM & External Power Lead The AiM RPM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free ...

AiM Solo 2 DL RPM & External Power Lead The AiM PRM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free cables Suitable for Solo 2 DL RPM External ...

Aim Solo 2 DL RPM & Power Cable (V02589020). The Aim Solo 2 DL CAN RS232 Lead is used to connect the Aim Solo 2 DL Dash Logger via CAN Connection to Engine ECU. For more ...

The AiM external power cable fits the AiM Solo 2 and Solo 2 DL GPS Lap Timers. It features a 5-pin 712 male binder connection, which goes into the Solo2/Solo 2 DL. The un-terminated wires allow you to connect to an external battery.

Power cable with wired car lighter socket for: Solo 2 and Solo 2 DL. Quick link Quick link English English Italiano Menu Compare ... Address : AiM Official Store Via Guido Cavalcanti, 8 20063 ...

Solo 2, power cable with car lighter socket, battey charger with AC adapter, mounting bracket with screws. ... AiM Solo 2/Solo 2 DL GPS laptimer/Dash logger aim ...

Technical AiM Solo 2 DL OBDII & External Power Connector Cable. 7 pin - 712 male binder connection; 2m Cable; OBDII Connector Pin: 2 - Positive bus line - SAE J1850 protocol: not ...

This pre-assembled cable with a 4-pin Deutsch DTM receptacle connector will allow you to directly plug your AiM Solo DL or Solo 2 DL into one of our 4-pin plug and play CAN-Bus adapters, providing: Cable Length: 2 metres. Notes:

The AiM external power cable to suit the AiM Solo 2 & Solo 2 DL GPS Lap Timer. Has a 5 pin Binder 712 male connector on one side and a 12V car lighter plug ...

Hi Guys, I finally got my Solo 2 DL working w/ my 2016 RSV4-RF and could successfully collect all telemetry data available in the ECU includes V4MP channels (atc level, lean angle, torque red, speed, throttle position, Inj ...

AiM Solo 2 DL OBDII & External Power Connector Cable The AiM OBDII 2m external power cable connects your Solo 2 DL to your ECU wiring. Key Features : 7 pin - 712 male binder connection OBDII connector Suitable for Solo 2 DL ...

Solo 2, power cable with car lighter socket, power cable with AC adapter, mounting bracket with screws, user manual & RaceStudio 3 software freely downloadable from AiM web site, AiM sticker. Solo 2 DL:

The power cable that comes with the AiM Solo 2 in the package is set up for a cigarette lighter connection, but this is a hard wire connection for true race cars. E-mail us ... AiM Solo 2 & Solo 2 DL Vehicle Power Wiring Harness Details: ...

Browse cables for powering Solo 2 and Solo 2 DL lap timers, and connecting Solo 2 DL to vehicle's ECU. Find the right cable at aimLapTimer ... AiM Solo 2 DL Cables for Honda ...

AiM Solo 2 DL CAN / RS232 2M External Power Cable Motorcycle The AiM CAN/RS232 2m external power cable connects your Solo 2 DL to your ECU wiring. Key Features : 7 pin - 712 male binder connection 6 non-terminated ...

Now you can power your AiM Solo 2 and Solo 2 DL for your entire endurance race without the need to charge the battery. The power cable that comes with the AiM Solo 2 in the package is set up for a cigarette lighter connection, but this ...

Browse cables for powering Solo 2 and Solo 2 DL lap timers, and connecting Solo 2 DL to vehicle's ECU. Find the right cable at aimLapTimer

Web: <https://www.bardzyndzalek.olsztyn.pl>

