

Can I plug my aim Solo / Solo 2 DL into a plug and play adapter?

Pre-assembled AiM Solo /Solo 2 DL cable to be used in conjunction with our plug and play adapters. This pre-assembled cable with mating 4-pin Deutsch DTM connector will allow you to directly plug your AiM Solo or Solo 2 DL into one of our plug and play adapters, providing: CAN-Hi and CAN-Low for logging of additional vehicle parameters

What is AIM Solo 2?

AIM Solo 2 is a revolutionary lap timer developed and tested by Akrapovic's top factory teams. It is simply the finest.

How does solo 2 DL work?

CAN, K-Line or RS232 connections. Solo 2 DL features an internal, high precision, 25 Hz, 4 constellations GPS receiver and an internal database including information about thousands of tracks all over the world: just switched ON, it automatically recognizes the track and gets the information about the Starting Line Position and the Time Zone.

What is the aim OBDII 2m external power cable used for?

The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables available for the Solo 2 DL. Others are the RS232/CAN and the RPM cable. Some of the OBDII protocol channels received are RPM, Vehicle speed, Fuel level, Throttle position.

Accessory for: Solo 2 DL More Info. [Quick link](#) [Quick link](#) [English](#) [English](#) [Italiano](#) ... [CAN/RS232 + external power cable 2 m for Solo 2 DL](#). [Add to Cart](#). [Previous](#). [Next](#). ... [Address : AiM Official](#) ...

Now you can power your AiM Solo2 DL for your entire endurance race without the need to charge the battery. The power cable that comes with the AiM Solo 2 in ...

Over USB the wanted track coordinates are transmitted to the SOLO 2 or the driven measurement data to the analyses to the PC. The version Solo 2 DL has additional an integrated data ...

The AiM external power cable fits the AiM Solo 2 and Solo 2 DL GPS Lap Timers. It features a 5-pin 712 male binder connection, which goes into the Solo2/Solo 2 DL. The un-terminated wires allow you to connect to an external battery. This ...

**AiM Solo 2 DL OBDII & External Power Connector Cable** The AiM OBDII 2m external power cable connects your Solo 2 DL to your ECU wiring. Key Features : 7 pin - 712 male binder ...

In addition to the dedicated bar pads, AiM designed specific applications to allow easy installation and

connection of Solo 2 DL on off road bikes. First of all, the AiM Taipan ECU kit. Also application kits for Honda, ...

AIM Solo is an automatic lap timer based on GPS technology. It locates its GPS position, identifies the track from the internal list of the main world tracks and starts ...

Solo 2, power cable with car lighter socket, battey charger with AC adapter, mounting bracket with screws. ...  
AiM Solo 2/Solo 2 DL GPS laptimer/Dash logger aim ...

AiM Solo 2 DL OBDII & External Power Connector Cable The AiM OBDII 2m external power cable connects your Solo 2 DL to your ECU wiring. Key Features : 7 pin - 712 male binder connection OBDII connector Suitable for Solo 2 DL ...

Solo 2 & Solo 2 DL External Power Cable. The AiM external power cable to suit the AiM Solo 2 & Solo 2 DL GPS Lap Timer. Has a 5 pin Binder 712 male connector on one side and a 12V car lighter plug on the other side. Suitable ...

The Aim Solo 2 lap timer is a powerful motorsport device that has been designed for both amateur and professional racers who want to enhance their motorsport performance using precise lap timing features. Extensive track database: Pre ...

SOLO 2 DL?? Aim????????????3000????????????? ...

3-axis acceleration sensor, gyroscope, magnetometer and an integrated 25 Hz GPS. The internal ring memory holds 4 GB and can record with a total sampling rate of 5.000 ...

AiM Solo 2 DL RPM & External Power Lead The AiM RPM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free cables Suitable for Solo 2 DL RPM External ...

AiM Solo 2 DL RPM & External Power Lead The AiM RPM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free ...

????: AiM Tech srl SOLO DL / SOLO 2 DLP& P ???? ?16,500 SOLO 2????????????????? ?20,900  
SOLO????????????????? ?14,300 ...

Solo 2 DL features an internal, high precision, 25 Hz, 4 constellations GPS receiver and an internal database including information about thousands of tracks all over the world: just switched ON, it automatically recognizes the track and ...

Solo 2, power cable with car lighter socket, battey charger with AC adapter, mounting bracket with screws.

User manual & Race Studio 3 software freely downloadable ...

The AiM external power cable to suit the AiM Solo 2 & Solo 2 DL GPS Lap Timer. Has a 5 pin Binder 712 male connector on one side and a 12V car lighter plug ...

AiM Solo 2 DL RPM & External Power Lead The AiM PRM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free cables Suitable for Solo 2 DL RPM External ...

Web: <https://www.bardzyndzalek.olsztyn.pl>

