

What is the aim OBDII 2m external power cable used for?

The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables available for the Solo 2 DL. Others are the RS232/CAN and the RPM cable. Some of the OBDII protocol channels received are RPM, Vehicle speed, Fuel level, Throttle position.

Can I plug my aim Solo / Solo 2 DL into a plug and play adapter?

Pre-assembled AiM Solo / Solo 2 DL cable to be used in conjunction with our plug and play adapters. This pre-assembled cable with mating 4-pin Deutsch DTM connector will allow you to directly plug your AiM Solo or Solo 2 DL into one of our plug and play adapters, providing: CAN-Hi and CAN-Low for logging of additional vehicle parameters

Can a can/rs232 DL / solo 2 DL plug into a CAN-bus adapter?

This cable is included with a CAN/RS232 Solo DL / Solo 2 DL but is unterminated and will not be able to directly plug into one of our 4-pin CAN-Bus adapters. If you already have one of these cables you can send it to us before (usable condition) or after (original condition) your order to receive a refund of the cable itself.

OBDII External Power Cable. The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables available for the Solo 2 DL. Others are the ...

This cable allows the AiM Solo 2 DL dash logger to be connected to the vehicle via the OBDII connector.
delivery status: available for immediate delivery article number description Info ...

AiM Sports Solo 2 Direct Power Cable. Price \$60. Quantity. Add to cart This item is a recurring or deferred purchase. By continuing, I agree to the cancellation policy and authorize you to charge my payment method at the prices, ...

This pre-assembled cable with a 4-pin Deutsch DTM receptacle connector will allow you to directly plug your AiM Solo 2 DL into one of our 4-pin plug and play CAN-Bus adapters, ...

SOLO o Solo (1) o Solo USB cable (2) o USB/AC power adapter (3) o Solo power cable with 2m wired car lighter socket (4) o Mounting bracket with screws (5) o Software ...

AiM Official Store Via Guido Cavalcanti, 8 20063 Cernusco sul Naviglio Milano Italy +39 02.9290571
orders@aim-sportline Accessory for: Solo 2 DL

The power cable that comes with the AiM Solo in the package is set up for a cigarette lighter connection, but this is a hard wire connection for true race cars. This harness ...

Solo 2 DL, battery charger with AC adapter, mounting bracket with screws, user manual. User manual & Race Studio 3 software freely downloadable from AiM web site. Spare ...

The AiM Solo 2 & Solo 2 DL mains charger and power lead. Motorsport EU 2-pin connection plug for charging from European mains power. The lead features a 5-pin 712 male binder connection and a 2-pin EU plug for mains connection.

OBDII External Power Cable. The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables ...

Aim Technologies Solo 2 Lap Timer samples data, predictive, theoretical and delta lap times, and has complete data recall with over 4,000 tracks on file. ... RPM external power cable (if your ...

The AiM external power cable fits the AiM Solo 2 and Solo 2 DL GPS Lap Timers. It features a 5-pin 712 male binder connection, which goes into the Solo2/Solo 2 DL. The un-terminated wires ...

AiM Solo 2 DL RPM & External Power Lead The AiM RPM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free cables Suitable for Solo 2 DL RPM External ...

Brand: AIM Sports This special AC adapter cable from AiM has a 5-pin 712 (screw-in) connector at one end. It has three different applications: MyChron5 kart dash: Use this cable to power your MyChron5 dash and charge the battery ...

AiM Taipan ECU can be connected to Solo 2 DL/XLog using this dedicated connection cable for a complete AiM Motocross system. ... Quick view CAN/RS232 + external power cable 2 m for Solo 2 DL. Accessory for: Solo 2 ...

This pre-assembled cable with a 4-pin Deutsch DTM receptacle connector will allow you to directly plug your AiM Solo DL or Solo 2 DL into one of our 4-pin plug and play CAN-Bus adapters, providing: Cable Length: 2 metres. Notes:

The AiM RPM cable is used for vehicles when the particular ECU is not supported. In the unlikely event, your particular ECU is not supported you can connect the Solo 2 DL to the coil RPM ...

Solo 2 DL: Solo 2 DL, power cable with AC adapter, mounting bracket with screws, user manual, software installation CD, AiM sticker. Concerning the cables you can choose among: CAN/K-Line/External power ...

Solo 2 DL in addition to what Solo 2 offers, provides some extremely useful features: ECU connection for receiving, showing and recording all the data directly from your ECU, both for CAN, RS232 and K-line

connections, low ...

AiM Solo 2 DL CAN / RS232 2M External Power Cable Motorcycle The AiM CAN/RS232 2m external power cable connects your Solo 2 DL to your ECU wiring. Key Features : 7 pin - 712 male binder connection 6 non-terminated ...

Web: <https://www.bardzyndzalek.olsztyn.pl>

